



02P. Clasp on the right from this view

4  
3

1  
2

公差 (General Tolerances)	公差 (mm)
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500

0.1/10	±Z
--------	----

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
SIZE: A4	mm / (inch)
DRAWING NO.:	TYPE: SCALE: SHEET



宁波三安电子科技有限公司  
Sanan Electrical Technology Co., Ltd

ITEM	NAME OF PART	MATERIAL	NOTES
5	Screw	Steel	M3/Zn Plated
4	Cage	Copper alloy	M3/N Plated
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/15	/	300/10
EC 标准 / EC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/3	II/2	II/2
额定电压/电流 / Rated Voltage(V)/Current(A)	/	320/18	/
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	/	4	/
扭矩范围 (硬线和软线) / Wire Range (rigid and flexible) (mm <sup>2</sup> / AWG)	/	M3, 0.59/5, 21	1.0~2.5/28~12
导线长度 / Stripping length (mm)	/	5.0/N=02~24P	/
使用温度范围 / Operating temperature (°C)	/	-40~+105	/
符合RoHS环保要求 / Conform to RoHS	/	Yes	/

SURFACE: