



O2P: Clasp on the right
from this view

5	Screw	Steel	M3/Zn Plated
4	Cage	Copper alloy	M3/Ni Plated
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准	UL Standard:	B	C D
额定电压/电流	Rated Voltage(V)/Current(A)	300/15	300/10
EC 标准	IEC Standard:		
过压类别	Overvoltage Category/污染等级	III/3	II/2 II/2
额定电压/电流	Rated Voltage(V)/Current(A)		320/18
额定脉冲电压	Rated Impulse Voltage(KV)		4
拧紧扭矩	Torque Tightening(N·m/Lb.in)	M3, 0.66/6.00	
线径范围	Wire Range(rigid and flexible)(mm ² /AWG)	1.0~2.5/28~12	
剥线长度	Stripping length(mm)	5.08	N=02~24P
使用温度范围	Operating temperature(°C)	-40~+105	
符合RoHS环保要求	Conform to RoHS	Yes	

MATERIAL: SURFACE:

MAT NO.:
STATUS:
APPD:
CHKD:
DRT:

NAME: **宁波三安电子科技有限公司**
Sanan Electrical Technology Co. Ltd
DRAWING NO.: **ZESAKA-5.08-XXP-1Y-1000A(H)**

SIZE: A4
SCALE: 1/1
TYPE: SHEET

公差 (General tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50	

0.1/10
±Z